

FC200

Inline or Undersink Water Filter



Rainfresh FC200 Drinking Water System is designed to deliver better quality drinking water at a fraction of the cost of bottled water. FC200 can be installed either undersink (connected to the cold water line of the kitchen faucet) or inline to serve 1 or 2 drinking water outlets to remove chlorine, sediment, taste and odour.

FC200 is ideal for homes, cottage/cabins, farms, offices, boats or RV.



PROTECTS AGAINST

- Chlorine, taste & odour (> 95%)
- Sediment (5 micron)



**Install inline to serve
1-2 drinking water
outlets**

OR



**Install undersink on
cold water pipe of
existing kitchen faucet**

Manufactured in Canada using high quality BPA-free materials, Rainfresh FC200 has the following features



Easy-open Housing – No Wrench Required !

Unique easy-open filter housing that does not require the use of a filter wrench. Simply grab the sump and turn 1/8th clockwise to open the sump, without using any tools.

Transparent Sump – See your filter working!

The clear transparent sump allows you to see the filter condition without turning the water off.



Installation Notes:

Unit Width (Inch)	Unit Height (Inch)	Unit Depth (Inch)	Connections
4.75"	13"	4.75"	3/4" Female NPT

- Connector kits for undersink installation (CK3) sold separately
- Not recommended for whole house installation

Specifications:

- Water Temperature Range : 4°C to 37°C (39 to 100°F)
- Feed Water Pressure : 10 to 100 psi* (68.9 to 689 kPa; 0.68 – 6.89 bar)
- Max Flow Rate – 1 US GPM (3.8 LPM)
- BPA-free materials

Replacement Cartridge:

Model CF2 – 5 micron (included).

Optional cartridge model CA1 for chloramine & chlorine reduction

Replacement Frequency:

1,000 US gal (3,785 L), or once every 6 months**

* -If water pressure exceeds the rated pressure, a pressure regulator & water hammer arrestor must be installed before the filter housing. It is recommended that the pressure regulator be set at 75 psi or less. ** - Cartridge life is directly dependent on water conditions. High sediment levels or water use may cause more frequent replacement



Replacement
Cartridge
Model : **CF2**



Optional
Cartridge
Model : **CA1**



Tested and certified by CSA International to NSF/ANSI 42 for reduction of chlorine, taste and odour, to CSA B483.1 and to NSF/ANSI 372 for low lead requirements

5 year limited warranty



Envirogard Products Limited

446 Major Mackenzie Drive East, Richmond Hill,
ON L4C 1J2, CANADA

Toll Free: 1-800-667-8072 • **Tel:** (905) 884 9388

Fax: (905) 884 3532 • **E-Mail:** info@rainfresh.ca

Web: www.rainfresh.ca