

This system has been tested according to NSF/ANSI 42 for reduction of the substances listed below in Table I. The concentration of the indicated substances in the water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI 42. The system is also tested and certified to CSA B483.1

Contaminant	Influent Challenge Concentration	Reduction Requirement	Average Reduction Efficiency
Standard 42 – Aesthetic Effects. Taste, Odour, Chlorine Reduction	2.0 mg/L ± 10%	≥ 50%	> 90%



TABLE- I

- Do not use on water that is microbiologically unsafe without adequate disinfection before or after the unit. The system may be used on disinfected water that may contain filterable cysts
- All testing performed under standard laboratory conditions. Actual performance may vary.

Note: Contaminants reduced by this filter are not necessarily present in water. Individuals requiring water of specific microbiological purity should follow the advice of their doctor or local health unit.

Technical Specifications

Replacement filter	-	Model CF2
Rated filter life	-	6 to 12 months or 1,000 US gal (3,785 Litres)
Rated service flow	-	0.75 US GPM (2.83 LPM)
Inlet/Outlet connections	-	3/4" FNPT
Operating Temp	-	4°C (39°F) min. to 38°C (100°F) max.
Working Pressure	-	20 psi (137 kPa) min. to 100 psi (689 kPa) max. *If water pressure can exceed 100 psi, a pressure regulator and water hammer arrestor must be installed before the filter. Recommended regulator setting is 60 - 75 psi.

General Operation & Maintenance: See product manual for maintenance instructions. User is responsible for general maintenance.

Warranty – Limited 5 year warranty. See product manual for details.

For replacement parts visit www.rainfreshstore.ca or contact your nearest Rainfresh dealer.



Dec 2016

Envirogard Products Limited

446, Major Mackenzie Drive East, Richmond Hill,
ON L4C 1J2, CANADA

Toll Free: 1800 667 8072

Tel: (905) 884 9388 Fax: (905) 884 3532.

Web: www.rainfresh.ca