

IGNC11U

ICE MACHINE WATER FILTER SYSTEM

Rainfresh®
ICEFRESH

For Cubers up to 750 lb/day & Flakers up to 1,500 lb/day

Rainfresh IGNC11U filter system is designed to protect ice making equipment from the harmful effects of scale build-up on evaporator plates, corrosion of metallic components and clogging of nozzles and solenoid valves caused by sediment. This reduces service costs and downtime substantially, leading to increased profits. The system is designed for optimal sanitation and performance of the ice machine by leaving the free chlorine in the water. This prevents microbiological growth within the ice machine.



PROTECTS AGAINST

- Scale build-up
- Sediment

IGNC11U is designed for situations where water has relatively low sediment. It is a single-stage system that:

- Features a polyphosphate feed to inhibit scale build-up in the ice machine
- Reduces sediment, dirt, rust and other visible particles in the water, down to 1 micron nominal

A water pressure gauge is included to monitor pressure variations and spikes. It also indicates cartridge plugging (when differential pressure exceeds 15 psi).



FEATURES & BENEFITS

- Reduces scale formation and sediment that cause frequent breakdowns of ice machines
- Extends life and reliability of ice machine
- Cartridge life monitor helps maintain unit
- Easy open housings
- Economical and easy to maintain



Electronic Cartridge Life Monitor

The IGNC11U filter system features an electronic "Cartridge Life Monitor" that sets off an LED indicator at the end of 6 months, signaling time to replace the filter cartridge. This unique feature helps users and service technicians maintain the efficiency of the filter system and reduce downtime.

Easy Open Housing

Rainfresh IGNC11U features an easy-open housing that does not require a wrench. Simply hold the sump by hand, rotate 1/8 turn and the sump detaches. It also features a manual pressure relief valve. This makes filter cartridge changes quick and easy with no need for a wrench or tools!




System Dimensions

Model	Unit Width	Unit Height	Unit Depth	Monitor Type
IGNC11U*	9.25" (235 mm)	13" (330 mm)	5" (127 mm)	Time

* - a) For cold water use only. This product is for commercial use only.

b) Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



Operating Specifications

Rated Capacity	: 10,000 US gal
Inlet/Outlet Connections	: 3/8"
Max. Service Flow Rate	: 1.5 US GPM (5.7 LPM)
Max. Temperature	: 100 F (38°C)
Max. Pressure	: 100 psi (689 kPa)**

** If pressure surges or water hammer conditions exist, a pressure regulator and/or water hammer arrestor should be installed.

Cartridge Specifications

Replacement Filter	Function	Micron Rating	Cartridge Life
MB10G01S	Reduction of sediment, inhibition of scale	1 μ	10,000 US gal or 6 months [^]

[^]Cartridge life may vary with water quality and usage.

Limited 1 year warranty



Jan 2019



Envirogard Products Limited

446 Major Mackenzie Drive East,
Richmond Hill, ON L4C 1J2, CANADA

Toll-free: 1 800 667 8072 ; Tel: (905) 884 9388; Fax: (905) 884 3532

E-Mail: info@rainfresh.ca ; Web: www.rainfresh.ca